



# Rapid Time Exports

*Rapid Like Lightning*



## APID-CRACK



### Specialization :-

*Amazing Expansive Capability*

*Works Efficiently and Cost Effectively*

*Non-Explosive & Environmentally Friendly*



### **What is Rapid-Crack / Expansive Mortar / Non Explosive Demolition?**

“Rapid-Crack” (Expansive Mortar) is a kind of powder with amazing 18,000 PSI expansive strength when mixed with common water. Poured into holes, “Rapid-Crack” breaks reinforced concrete & rock safely and quietly, while providing SILENT cracking, Since “Rapid-Crack” provides controlled demolition according to drilling patterns, it is very easy to break reinforced concrete and all kinds of stone into desired sizes and shapes, without noise, vibration or dust.



## What Can "Rapid-Crack" help with you?



**Sand Stone Quarrying**



**Marble Quarrying**



**Granite Quarrying**



**Non Explosive Demolition Powder**





**Stone Cutting**



**Rock Breaking**

### **Use and Filling of Rapid-Crack**

Mix well and pour into holes while agitating the hole to make sure no air gaps are in the hole. Example: Using a piece of rod or stick to poke holes. The cracks appear in 40-60 min. after filling, depending on the weather, rocks and concrete type. The cracks become wider within time (Maximum 48 hours expanding time).



Depending on different working temperature, there are four types of crack agent for your choice.

SCA Type	Temperature (Celsius)	Temperature (Fahrenheit)
Type-1	25-40°C	77-104°F
Type-2	10-25°C	50-77°F
Type-3	-5-10°C	23-50°F
Type-4	40-50°C	104-122°F

### Packaging :

1.	<b>First Step</b>	5kg in Plastic Bag.
2.	<b>Second Step</b>	4 Plastic Bags in 1 Carton
3.	<b>Third Step</b>	50-60 Cartons on every wooden or plastic pallet.

